



FRONIUS GALVO

/ The future-proof inverter for small self-consumption systems.



/ SnapInverter Technology



/ HF transformer switchover



/ Integrated data communication



/ Smart Grid Ready



/ Zero feed-in



/ With power categories ranging from 1.5 to 3.1 kW, the Fronius Galvo is perfect for households – and is especially suitable for self-consumption systems. The integrated energy management relay allows the self-consumption component to be maximised. A host of other smart features make the Fronius Galvo one of the most future-proof inverters in its class: for example, the integrated datalogging, the simple connection to the internet by WLAN, or the plug-in card technology for retrofitting additional functions.


TECHNICAL DATA FRONIUS GALVO

INPUT DATA	GALVO 1.5-1	GALVO 2.0-1	GALVO 2.5-1	GALVO 3.0-1 ¹⁾	GALVO 3.1-1
Number of MPP trackers			1		
Max. input current ($I_{dc\ max}$)	13.3 A	17.8 A	16.6 A	19.8 A	20.7 A
Max. array short circuit current	20.0 A	26.8 A	24.8 A	29.6 A	31.0 A
DC input voltage range ($U_{dc\ min} - U_{dc\ max}$)	120 - 420 V			165 - 550 V	
Feed-in start voltage ($U_{dc\ start}$)	140 V			185 V	
Usable MPP voltage range	120 - 335 V			165 - 440 V	
Number of DC connections			3		
Max. PV generator output ($P_{dc\ max}$)	3.0 kWpeak	4.0 kWpeak	5.0 kWpeak	6.0 kWpeak	6.2 kWpeak
OUTPUT DATA	GALVO 1.5-1	GALVO 2.0-1	GALVO 2.5-1	GALVO 3.0-1 ¹⁾	GALVO 3.1-1
AC nominal output ($P_{ac,r}$)	1,500 W	2,000 W	2,500 W	3,000 W	3,100 W
Max. output power	1,500 VA	2,000 VA	2,500 VA	3,000 VA	3,100 VA
AC output current ($I_{ac\ nom}$)	6.5 A	8.7 A	10.9 A	13.0 A	13.5 A
Grid connection (voltage range)	1-NPE 230 V (+17 % / -20 %)				
Frequency (frequency range)	50 Hz / 60 Hz (45 - 65 Hz)				
Total harmonic distortion	< 4 %				
Power factor ($\cos \varphi_{ac,r}$)	0.85 - 1 ind. / cap.				
GENERAL DATA	GALVO 1.5-1	GALVO 2.0-1	GALVO 2.5-1	GALVO 3.0-1 ¹⁾	GALVO 3.1-1
Dimensions (height x width x depth)			645 x 431 x 204 mm		
Weight	16.4 kg		16.8 kg		
Degree of protection	IP 65				
Protection class	1				
Overtoltage category (DC / AC) ²⁾	2 / 3				
Night-time consumption	< 1 W				
Inverter concept	HF transformer				
Cooling	Regulated air cooling				
Installation	Indoor and outdoor installation				
Ambient temperature range	-25 - +50 °C				
Permitted humidity	0 to 100 %				
Max. altitude	2,000 m / 3,500 m (unrestricted / restricted voltage range)				
DC connection technology	3x DC+ and 3x DC- screw terminals 2.5 - 16 mm ²				
AC connection technology	3-pin AC screw terminals 2.5 - 16 mm ²				
Certificates and compliance with standards	ÖVE / ÖNORM E 8001-4-712, AS 4777-2, AS 4777-3, AS3100, DIN V VDE 0126-1-1/A1, VDE AR N 4105, IEC 62109-1-2, IEC 62116, IEC 61727, CER 06-190, CEI 0-21, EN 50438, G83, G59, NRS 097				


¹⁾ Available for countries where 3 kW restrictions apply. ²⁾ Testing to IEC 62109-1.

Further information regarding the availability of the inverters in your country can be found at www.fronius.com.

FRONIUS GALVO 3.1-1 EFFICIENCY CURVE



FRONIUS GALVO 3.1-1 TEMPERATURE DERATING



TECHNICAL DATA FRONIUS GALVO

EFFICIENCY	GALVO 1.5-1	GALVO 2.0-1	GALVO 2.5-1	GALVO 3.0-1 ¹⁾	GALVO 3.1-1
Max. efficiency	95.9 %	96.0 %		96.1 %	
European efficiency (η_{EU})	94.5 %	94.9 %	95.2 %	95.4 %	95.4 %
MPP adaptation efficiency	> 99.9 %				
PROTECTION DEVICES	GALVO 1.5-1	GALVO 2.0-1	GALVO 2.5-1	GALVO 3.0-1 ¹⁾	GALVO 3.1-1
DC insulation measurement	Warning/shutdown (depending on country setup) at $R_{ISO} < 600 \text{ k}\Omega$				
Overload behavior	Operating point shift, power limitation				
DC disconnecter	Included				
Reverse polarity protection	Yes				
INTERFACES	GALVO 1.5-1	GALVO 2.0-1	GALVO 2.5-1	GALVO 3.0-1 ¹⁾	GALVO 3.1-1
WLAN / Ethernet LAN	Fronius Solar.web, Modbus TCP SunSpec, Fronius Solar API (JSON)				
6 inputs and 4 digital inputs/outputs	Interface to ripple control receiver				
USB (A socket) ²⁾	Datalogging, inverter update via USB flash drive				
2x RS422 (RJ45 socket) ²⁾	Fronius Solar Net				
Signalling output ²⁾	Energy management (floating relay output)				
Datalogger and Webserver	Included				
External input ²⁾	SO-Meter Interface / Input for overvoltage protection				
RS485	Modbus RTU SunSpec or meter connection				

¹⁾ Available for countries where 3 kW restrictions apply. ²⁾ Also available in the light version. Further information and technical data can be found at www.fronius.com.

/ Perfect Welding / Solar Energy / Perfect Charging

WE HAVE THREE DIVISIONS AND ONE PASSION: SHIFTING THE LIMITS OF POSSIBILITY.

/ Whether welding technology, photovoltaics or battery charging technology – our goal is clearly defined: to be the innovation leader. With around 3,700 employees worldwide, we shift the limits of what's possible - our record of over 800 granted patents is testimony to this. While others progress step by step, we innovate in leaps and bounds. Just as we've always done. The responsible use of our resources forms the basis of our corporate policy.

Further information about all Fronius products and our global sales partners and representatives can be found at www.fronius.com

v06 Apr 2016 EN

Fronius India Private Limited
GAT no 312, Nanekarwadi
Chakan, Taluka - Khed District
Pune 410501
India
pv-sales-india@fronius.com
www.fronius.in

Fronius Australia Pty Ltd.
90-92 Lambeck Drive
Tullamarine VIC 3043
Australia
pv-sales-australia@fronius.com
www.fronius.com.au

Fronius UK Limited
Maidstone Road, Kingston
Milton Keynes, MK10 0BD
United Kingdom
pv-sales-uk@fronius.com
www.fronius.co.uk

Fronius International GmbH
Froniusplatz 1
4600 Wels
Austria
pv-sales@fronius.com
www.fronius.com